

# BERMINGHAMMER

FOUNDATION EQUIPMENT



## BHD-40 Drill



### Features

- High Torque Rock Drill
- Available For Reverse Circulation
- Available For Direct Circulation
- Environmentally friendly (no-drip operation, bio-fuels and oils)
- Optimized for DTHH operations
- 7" Discharge
- Air Swivel 300 PSI
- 100 ton Thrust Bearings
- 100 ton Extraction Bearings
- Positive Lubrication
- Hydraulic Crowd Available

### Operational Specifications

|                    |                     |
|--------------------|---------------------|
| Maximum Torque:    | 40,000 ft-lbs       |
| Maximum Power:     | 170 HP Continuous   |
| Maximum Speed:     | 30 RPM              |
| Maximum Crowd:     | 50 Tons             |
| Maximum Auger Dia: | 30", 18" Continuous |

### Hydraulic Power Requirements

|                   |                            |
|-------------------|----------------------------|
| Hydraulic Power:  | 200 HP Minimum             |
| Flow:             | 80 GPM                     |
| Pressure:         | 4800 PSI                   |
| Hoses:            | 2x 2" 6 wire, 1x 1" 3 wire |
| Operating Weight: | 15,000 lbs                 |

**BERMINGHAMMER**

FOUNDATION EQUIPMENT



Toll Free (Canada & USA 1.800.668.9432)  
www.berminghammer.com | bfssales@berminghammer.com